

# Sunmoon Battery

## ER26500

**Lithium Thionyl Chloride Battery [Bobbin Type]**  
**Li/SOCI2 3.6V**




### • Electrical Specification

<b>Nominal Capacity[3mA~2V]</b>	<b>8.5Ah</b>
<i>The discharge capacity of battery depends on the environment temperature and the terminated voltage of the battery.</i>	
<b>Nominal Voltage</b>	<b>3.6V</b>
<b>Maximum Continuous Current</b>	<b>100mA</b>
<b>Maximum Pulse Current</b>	<b>200mA</b>
<i>Under temperature of 23±2°C, the battery starts to discharge with 10uA base current. The battery releases one pulse 200mA/0.1secs every 2 minutes during its discharging and the battery voltage shall not be less than 2.7V. The voltage value depends on pulse characteristics, temperature and the usage of the batteries.</i>	
<b>Weight</b>	<b>53g</b>
<b>Operating Temperature</b>	<b>-55°C ~ +85°C</b>

### • Advantages

- High energy density over 620wh/kg [highest among all the chemical batteries]
- Open circuit voltage ≥ 3.65V, and operating voltage ranging from 3.3~3.6V
- Wide operating temperature range: -55°C ~ +85°C
- Long storage life over 10 years [under normal room temperature]
- Suitable to operate under long-term tiny current with stable voltage

### • Main Applications




**Customer Satisfaction is the Purpose We Always Adhere to,  
Continuous Improvement is the Direction We Always Pursue!**

# Sunmoon Battery ER26500


**Lithium Thionyl Chloride Battery [Bobbin Type]  
Li/SOCI<sub>2</sub> 3.6V**





Typical Discharge Profiles at +23±2°C



Restored Capacity Versus Current and Temperature [2.0V cut-off]



Voltage Plateau Versus Current and Temperature



## • Available Terminations

- S: Standard Termination
- T: Solder Tabs
- P: Axial Pins
- Customized terminations are available

## • Warning

- Do not expose the battery to open flame, inflammable and explosive articles.
- Do not recharge, short-circuit, disassemble, incinerate the battery or heat the battery to more than 100°C.
- Do not use the battery beyond the permitted temperature range.

**Wuhan Sunmoon Battery Co., Ltd.**

Tel: +86-27-84732116 84730089  
Add: No.231, Xingsan Road, Hannan District, Wuhan, Hubei Province, China

Post: 430090  
Web: [www.sunmoonbat.com](http://www.sunmoonbat.com)  
Email: [info@sunmoonbat.com](mailto:info@sunmoonbat.com)