



Pony Testing International Group

Report No.: MPIS6EUJ78676716a

MSDS Report

Sample Name
& Model

Lithium Manganese Dioxide Battery CR123A

Applicant

Wuhan Sunmoon Battery Co.,Ltd

Address

No.231,Xingsan Road,Shamao Street,Hannan
District,Wuhan,Hubei



No.: MPIS6EUJ78676716
Code: ttiyanqkh



北京实验室: (010)83055000	长春实验室: (0431)85150908	石家庄实验室: (0311)85376660	武汉实验室: (027)83997127
上海实验室: (021)64851999	大连实验室: (0411)87336618	西安实验室: (029)89608785	合肥实验室: (0551)63843474
青岛实验室: (0532)88706866	哈尔滨实验室: (0451)58627755	呼和浩特实验室: (0471)3450025	广州实验室: (020)89224310
深圳实验室: (0755)26050909	郑州实验室: (0371)69350670	杭州实验室: (0571)85806807	厦门实验室: (0592)5568048
天津实验室: (022)23607888	新疆实验室: (0991)6684186	宁波实验室: (0574)87977185	成都实验室: (028)87702708
苏州实验室: (0512)62997900			

声明 Statement

1. 本证明/报告的结论仅对委托方所送样品负责。
The conclusion of the certificate/report is responsible for the provided sample only.
2. 委托方必须如实提供样品, 申报和声明资料, 并保证与实际相符, 否则由委托方承担由此导致的全部后果和责任。
The applicant shall provide accurately and truly the description and statement of the sample, shall guarantee to match the sample and real situation which they provided and declared. Otherwise the application shall bear any relevant consequences and responsibility.
3. 如委托方提供的样品及相关资料存在虚假、伪造等情形, 所造成的全部后果和责任由委托方承担。
In case the sample and documents provided involved in the situation of fake and forgery, any consequences and responsibility caused by this shall be undertaken by applicant.
4. 本证明/报告私自转让、盗用、冒用、涂改、未经本单位批准的复制(全文复制除外)或以其它任何形式的篡改均属无效, 本单位将对上述行为追究其相应的法律责任。
The certificate/report is invalid in case of illegal transfer, embezzlement, imposture, modification or any altering, reproducing except in full, without approval of PONY. PONY shall investigate and affix the applicant's legal liability accordingly.
5. 本证明/报告不考虑国家及经营人差异。
The certificate/report takes no account of the differences of countries and applicants.
6. 本单位有权在完成证明/报告后处理委托方所送样品。
PONY has the right to dispose the provided sample after approval of the certificate/report.

.....
▲ 防伪说明:

- (1) 报告编号是唯一的;
 - (2) 报告采用特制防伪纸张印制, 纸张表面带有“PONY”防伪纹路, 该防伪纹路不支持复印, 即复制件不会带有“PONY”防伪纹路;
 - (3) 报告采用的防伪纸张内部亦加带有高科技“PONY”防伪水印, 只有在验钞机等紫外线照射下方可显出无色荧光防伪字样。
-



全国服务热线
400-819-5688

WWW.PONYTEST.COM

扫描二维码

关注谱尼测试微信

公众号 PONY4008195688



北京实验室: (010) 83055000	武汉实验室: (027) 83997127	哈尔滨实验室: (0451)58627755
上海实验室: (021) 64851999	长春实验室: (0431)85150908	石家庄实验室: (0311)85376660
青岛实验室: (0532)88706866	大连实验室: (0411)87336618	乌鲁木齐实验室: (0991) 6684186
深圳实验室: (0755)26050909	郑州实验室: (0371)69350670	呼和浩特实验室: (0471) 3450025
天津实验室: (022) 23607888	西安实验室: (029) 89608785	杭州实验室: (0571)85806807
苏州实验室: (0512)62997900	太原实验室: (0351) 7555762	宁波实验室: (0574)87977185
		温州实验室: (0577)88271060
		合肥实验室: (0551)63843474
		广州实验室: (020) 89224310
		厦门实验室: (0592)5568048
		成都实验室: (028) 87702708



Pony Testing International Group

Report No.: MPIS6EUJ78676716a Date: 2021-01-13 Page 1 of 10

Material Safety Data Sheet

Reference to ST/SG/AC.10/30/Rev.8 (GHS)

Section 1 - Chemical Product and Company Identification

Chemical Product Identification

Sample Name: Lithium Manganese Dioxide Battery**Sample Model:** CR123A**Recommended Uses:** Used for equipment**Restrictions on Use:** N/A**Supplier Name:** Wuhan Sunmoon Battery Co.,Ltd**Address:** No.231,Xingsan Road,Shamao Street,Hannan District,Wuhan,Hubei**Phone Number:** 15871795153**FAX:** 027-84732179**E-mail:** 549191875@qq.com**Emergency Phone Number:** 027-84732116

Section 2 - Hazards Identification

Emergency overview: This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

Classification according to GHS

Acute toxicity, oral (4)

Acute toxicity, inhalation (4)

Skin corrosion/irritation (1A-1C)

Serious eye damage/eye irritation (1)

Sensitisation, skin (1, 1A, 1B)

Carcinogenicity (2)

Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Specific target organ toxicity, repeated exposure (2)

Label elements

Hazard pictogram(s):**Signal word:**

Danger

Hazard statement(s):

H302 Harmful if swallowed



Pony Testing International Group

Report No.: MPIS6EUJ78676716a Date: 2021-01-13 Page 2 of 10

H332 Harmful if inhaled

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H317 May cause an allergic skin reaction

H351 Suspected of causing cancer

H335 May cause respiratory irritation

H373 May cause damage to organs through prolonged or repeated exposure

Precautionary statement(s):

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust, fume, gas, mist, vapours, spray.

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

Response:

P330 Rinse mouth.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P363 Wash contaminated clothing before reuse.

P310 Immediately call a POISON CENTER.

P321 Specific treatment (See additional emergency instructions).

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302 + P352 IF ON SKIN: Wash with plenty of water.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Send contents to approved waste treatment plants.

Other hazards

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11

Environmental hazards: See Section 12



Section 3 – Composition/Information on Ingredients

Chemical characterization: Mixture

Chemical Composition	CAS No.	EC#	Weight (%)
Lithium	7439-93-2	231-102-5	2.8
Manganese dioxide	1313-13-9	215-202-6	21.4
Electrolyte	---	---	12.5
Carbon black	1333-86-4	215-609-9	3.37
Stainless Steel, Nickel and inert material	---	---	59.93

Section 4 - First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Small Fire: Dry chemical, soda ash, lime or sand. Large Fire: DRY sand, dry chemical, soda ash or lime or withdraw from area and let fire burn. Move containers from fire area if you can do it without risk.



Pony Testing International Group

Report No.: MPIS6EUJ78676716a Date: 2021-01-13 Page 4 of 10

Unsuitable extinguishing media:

Water or foam.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Produce flammable gases on contact with water. May ignite on contact with water or moist air. Some react vigorously or explosively on contact with water. May be ignited by heat, sparks or flames. May re-ignite after fire is extinguished. Runoff may create fire or explosion hazard.

Specific protective actions for fire-fighters:

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6 - Accidental Release Measures

Personal precautions:

As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids. Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Ventilate the area before entry.

Protective equipment:

No data available.

Emergency procedures:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do it without risk. Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. DO NOT GET WATER on spilled substance or inside containers. Small Spill: Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Dike for later disposal; do not apply water unless directed to do so. Powder Spill: Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST.

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

For all waste handling must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storage



Precautions for safe handling:

Avoid short circuiting the battery. Avoid mechanical damage of the battery. Do not open or disassemble. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

Section 8 - Exposure Controls/Personal Protection

Control parameters

CAS No.	ACGIH	NIOSH	OSHA
7439-93-2	N/A	N/A	N/A
1313-13-9	N/A	N/A	N/A
1333-86-4	TLV-TWA 3mg/m ³	REL-TWA 3.5mg/m ³	PEL-TWA 3.5mg/m ³

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment:

Respiratory protection: Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact.

Eye Protection: Wear safety goggles or eye protection combined with respiratory protection.

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Colour: Silver and Green.

Physical State: Cylindrical.

Odour: Not available.



Pony Testing International Group

Report No.: MPIS6EUJ78676716a Date: 2021-01-13 Page 6 of 10

Odour threshold:	Not available.
pH:	Not available.
Melting point/freezing point:	Not available.
Initial boiling point and boiling range:	Not available.
Flash Point:	Not available.
Evaporation rate:	Not available.
Flammability (solid, gas):	Not available.
Explosion Limits (vol% in air):	Not available.
Vapour pressure, kPa at 20°C:	Not available.
Vapor density:	Not available.
Density/Relative density (water = 1):	Not available.
Solubility(ies):	Not available.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
Viscosity:	Not available.
Other information:	
Voltage	3.0V
Electric capacity	1.5Ah
Aggregate lithium content	0.5g

Section 10 - Stability and Reactivity

Reactivity: No data available.

Chemical stability: Stable.

Possibility of hazardous reactions: No data available.

Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.

Incompatible materials: Oxidizing agents, acid base.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 11 - Toxicological Information

Acute Toxicity:

CAS No.	LC50/LD50
7439-93-2	No data available.
1313-13-9	No data available.
1333-86-4	No data available.



Pony Testing International Group

Report No.: MPIS6EUJ78676716a Date: 2021-01-13 Page 7 of 10

Skin corrosion/irritation: No data available.

Serious eye damage/irritation: No data available.

Respiratory or Skin sensitization: No data available.

Germ Cell mutagenicity: No data available.

Carcinogenicity: No data available.

Reproductive toxicity: No data available.

Specific target organ toxicity-Single exposure: No data available.

Specific target organ toxicity-Repeated exposure: No data available.

Aspiration hazard: No data available.

Information on the likely routes of exposure: No data available.

Eye: No data available.

Skin: No data available.

Ingestion: No data available.

Inhalation: No data available.

Section 12 - Ecological Information

Ecological Toxicity: No data available.

Persistence and degradability: No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Other adverse effects: No data available.

Section 13 - Disposal Considerations

Disposal methods:

Recommendation:

Consult state, local or national regulations to ensure proper disposal.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

Section 14 - Transport Information

UN or ID Number

IMDG

UN3090

Model Regulation

UN3090



Pony Testing International Group

Report No.: MPIS6EUJ78676716a Date: 2021-01-13 Page 8 of 10

Proper Shipping Name/Description	
IMDG	Lithium metal batteries
Model Regulation	LITHIUM METAL BATTERIES
Class or Div. (Sub Hazard)	
IMDG	9
Model Regulation	9
Packing Group	
IMDG	N/A
Model Regulation	N/A
Hazard Label	
IMDG	N/A
Model Regulation	N/A
Environmental hazards	
Marine pollutant:	No
Special precautions for user	No information available.

Transport information: The Lithium Manganese Dioxide Battery CR123A has passed the test UN38.3, according to the report ID: MMIGBCFM14848521a.

According to the special provision 188 of IMDG (39-18) or the special provision 188 of <<Recommendations On The Transport Of Dangerous Goods-Model Regulations>> (21st), the goods are not subject to other provision of this code.

Separate batteries to prevent short-circuiting. and they should be packed in strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames.

Transport Fashion: by sea, by railway, by road.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	TSCA	IECSC	DSL/NDSL	EINECS/ ELINCS/ NLP
7439-93-2	Listed	Listed	Listed DSL	Listed
1313-13-9	Listed	Listed	Listed DSL	Listed
1333-86-4	Listed	Listed	Listed DSL	Listed



Section 16 - Other Information

Issue Date: 2021-01-13

Issue Department: Technical department

Modification record:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:

CAS: (Chemical Abstracts Service);

EC: (European Commission);

ACGIH: (American Conference of Governmental Industrial Hygienists);

NIOSH: (US National Institute for Occupational Safety and Health);

OSHA: (US Occupational Safety and Health);

TLV: (Threshold Limit Value)

TWA: (Time Weighted Average);

STEL: (Short Term Exposure Limit);

PEL: (Permissible Exposure Level);

REL: (Recommended Exposure Limit);

PC-STEL: (Permissible concentration-short time exposure limit);

PC-TWA: (Permissible concentration-time weighted average);

LC50: (Lethal concentration, 50 percent kill);

LD50: (Lethal dose, 50 percent kill);

IARC: (International Agency for Research on Cancer);

EC50: (Median effective concentration);

BCF: (Bioconcentration Factor);

BOD: (Biochemical oxygen demand);

NOEC: (No observed effect concentration);

NTP: (US National Toxicology Program);

RTECS: (Registry of Toxic Effects of Chemical Substances);

IATA: (International Air Transport Association);

IMDG: (International Maritime Dangerous Goods);

TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations);

TOC: (Total Organic Carbon);



Pony Testing International Group

Report No.: MPIS6EUJ78676716a Date: 2021-01-13 Page 10 of 10

TSCA: (Toxic Substances Control Act of USA);
 DSL: (the Domestic Substances List of Canada);
 NDSL: (the Non-domestic Substances List of Canada)

The original English report which report No. is MPIS6EUJ78676716 be replaced by this report, and it will be canceled immediately and doesn't have any legal validity. Please compliance with this report.

2021-01-13

End of report