



Years Warranty*

ANSMANN Powerline Vario X

Universal charger for Li-Ion/Li-Po rechargeable battery packs or 2× AA or AAA NiMH rechargeable batteries

Features

- Universal charger for Li-Ion / Li-Po rechargeable battery packs (3.6V/3.7V or 7.2V/7.4V) or 2× 1.2V AA or AAA NiMH rechargeable batteries
- Incl. 100 cm Micro-USB charge cable, which can be used with almost any USB connection
- Moveable contacts for individual adaptation to most Li-Ion/Li-Po rechargeable battery packs
- Automatic voltage and polarity detection for Li-Ion/Li-Po rechargeable batteries
- Automatic charge start after rechargeable battery is inserted
- Microcontroller-monitored charge control
- Short-circuit protection, reverse polarity protection, automatic defective battery detection, safety timer
- Automatic battery-full detection
- Automatic changeover to pulse maintenance charging with NiMH rechargeable batteries
- Display of the charge status via LCD display
- Charge current: max. 600 mA for Li-Ion/Li-Po, 1000 mA for NiMH
- Compact and light, ideal for travelling



Charging current



Defect detection



Overload protection



Automatic Shutdown



Powered by USB



LCD display



Article number: 1001-0085
 Product content: Powerline Vario X, Micro-USB charge cable, operating instructions
 Customs tariff number: 85044055900
 Packing Unit: 4 (208 × 95 × 150 mm)



Specifications

| | |
|---------------------------|---|
| Input voltage | 5V DC |
| For worldwide use | Yes |
| Chargeable cell chemistry | Nickel metal hydride / Nickel-cadmium / Lithium ion / Lithium polymer |
| Chargeable cells | AAA / HR03 / AA / HR6 / battery pack |
| Charging current AAA | 1000 mA |
| Charging current AA | 1000 mA |
| Charging current lithium | max. 600 mA |
| Microprocessor control | Yes |
| Temperature monitoring | No |
| Safety timer | only round cells |
| LCD display | Yes |
| Single shaft monitoring | No |
| Overload protection | Yes |
| Discharge function | No |
| Refresh function | No |
| Battery defect detection | Yes |
| Quick capacity test | Yes |
| Color | black |
| Packaging | cardboard box |
| Operating temperature | 0 - 25 °C |
| Storage temperature | -25 - 70 °C |